



Tip Chart for CP-11TT – Pg. 1

Tip PN & Description	Pressure (PSI)	Capacity 1-Nozzle (GPM)	Top View of Tip	Full View of Tip
CP256-0006 Straight Stream (lite gray)	30	.52		
	40	.60		
	50	.67		
	60	.73		
CP256-0008 Straight Stream (white)	30	.69		
	40	.80		
	50	.89		
	60	.98		
CP256-0010 Straight Stream (battleship gray)	30	.87		
	40	1.0		
	50	1.18		
	60	1.23		
CP256-0012 Straight Stream (orange)	30	1.00		
	40	1.20		
	50	1.42		
	60	1.47		
CP256-0015 Straight Stream (lime green)	30	1.30		
	40	1.50		
	50	1.68		
	60	1.84		
CP256-0020 Straight Stream (lite yellow)	30	1.73		
	40	2.00		
	50	2.24		
	60	2.45		
CP256-0025 Straight Stream (bright blue)	30	2.17		
	40	2.50		
	50	2.95		
	60	3.06		

Images enlarged to show detail.



Parts may be ordered online: www.LaneAv.com



Tip PN & Description	Pressure (PSI)	Capacity 1-Nozzle (GPM)	Top View of Tip	Side View of Tip	Full View of Tip
CP256-8002 80° Tip (Only available in 80°) (yellow)	30 40 50 60	.17 .20 .22 .24			
CP256-8003 80° Tip (Only available in 80°) (royal blue)	30 40 50 60	.26 .30 .34 .37			
CP256-2004 20° Tip (red)	30 40 50 60	.35 .40 .45 .49			
CP256-4004 40° Tip (red)	30 40 50 60	.35 .40 .45 .49			
CP256-8004 80° Tip (red)	30 40 50 60	.35 .40 .45 .49			
CP256-110-4 110° Tip (red)	30 40 50 60	.35 .40 .45 .49			
CP256-8005 80° Tip (Only available in 80°) (brown)	30 40 50 60	.43 .50 .56 061			

Images enlarged to show detail.



Tip PN & Description	Pressure (PSI)	Capacity 1-Nozzle (GPM)	Top View of Tip	Side View of Tip	Full View of Tip
CP256-2006 20° Tip (lite gray)	30 40 50 60	.52 .60 .67 .73			
CP256-4006 40° Tip (lite gray)	30 40 50 60	.52 .60 .67 .73			
CP256-8006 80° Tip (lite gray)	30 40 50 60	.52 .60 .67 .73			
CP256-110-6 110° Tip (lite gray)	30 40 50 60	.52 .60 .67 .73			
CP256-2008 20° Tip (white)	30 40 50 60	.69 .80 .89 .98			
CP256-4008 40° Tip (white)	30 40 50 60	.69 .80 .89 .98			
CP256-8008 80° Tip (white)	30 40 50 60	.69 .80 .89 .98			
CP256-110-8 110° Tip (white)	30 40 50 60	.69 .80 .89 .98			

Images enlarged to show detail.



Tip PN & Description	Pressure (PSI)	Capacity 1-Nozzle (GPM)	Top View of Tip	Side View of Tip	Full View of Tip
CP256-2010 20° Tip (battleship gray)	30	.87			
	40	1.00			
	50	1.18			
	60	1.23			
CP256-4010 40° Tip (battleship gray)	30	.87			
	40	1.0			
	50	1.18			
	60	1.23			
CP256-8010 80° Tip (battleship gray)	30	.87			
	40	1.0			
	50	1.18			
	60	1.23			
CP256-2012 20° Tip (orange)	30	1.00			
	40	1.20			
	50	1.42			
	60	1.47			
CP256-4012 40° Tip (orange)	30	1.00			
	40	1.20			
	50	1.42			
	60	1.47			
CP256-8012 80° Tip (orange)	30	1.00			
	40	1.20			
	50	1.42			
	60	1.47			
CP256-2015 20° Tip (lime green)	30	1.30			
	40	1.50			
	50	1.68			
	60	1.84			
CP256-4015 40° Tip (lime green)	30	1.30			
	40	1.50			
	50	1.68			
	60	1.84			
CP256-8015 80° Tip (lime green)	30	1.30			
	40	1.50			
	50	1.68			
	60	1.84			

Tip PN & Description	Pressure (PSI)	Capacity 1-Nozzle (GPM)	Top View of Tip	Side View of Tip	Full View of Tip
CP256-2020 20° Tip (lite yellow)	30	1.73			
	40	2.00			
	50	2.24			
	60	2.45			
CP256-4020 40° Tip (lite yellow)	30	1.73			
	40	2.00			
	50	2.24			
	60	2.45			
CP256-8020 80° Tip (lite yellow)	30	1.73			
	40	2.00			
	50	2.24			
	60	2.45			
CP256-4025 40° Tip (bright blue)	30	2.17			
	40	2.50			
	50	2.95			
	60	3.06			
CP256-8025 80° Tip (bright blue)	30	2.17			
	40	2.50			
	50	2.95			
	60	3.06			
CP256-4030 40° Tip (tan)	30	2.60			
	40	3.00			
	50	3.54			
	60	3.67			
CP256-8030 80° Tip (tan)	30	2.60			
	40	3.00			
	50	3.54			
	60	3.67			
CP256-6040 60° Tip (clear)	40	4.00			

Images enlarged to show detail.

